

MASTER LEDbulb

MASTER LEDbulb DT 9-60W E27 A60 CL

The MASTER LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to the incandescentlamp. They are particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 holder and designed for retrofit replacement of incandescent bulbs, MASTER LEDbulb delivers huge energy savings and minimizes maintenance cost without any compromise on light quality. They can be used together with most leading-edge dimmers, enabling further efficiencies while helping to create the desired atmosphere.

Product data

• General Characteristics

| Cap-Base | E27 |
|------------------|--------------|
| Bulb | A60 [A 60mm] |
| Bulb Finish | Clear |
| Rated Lifetime | 25000 hr |
| (hours) | |
| Nominal Lifetime | 25000 hr |
| hours | |

• Light Technical Characteristics

| Color Code Color Designation (text) | WW Warm White |
|---|-------------------------------|
| Luminous Flux | 806 Lm |
| Color rendering | 80 |
| index | |
| Luminous Efficacy | 89 Lm/W |
| Lamp | |
| Color Temperature | 2200-2700 K [CCT 2200K-2700K] |
| Rated Luminous Flux | 806 Lm |
| LLMF - end nominal | 70 % |
| lifetime | |
| Colour consistency | 6 steps |
| | |

• Electrical Characteristics

| Wattage | 9 W |
|--------------------|-------------|
| Wattage Technical | 9 W |
| Voltage | 220-240 V |
| Line Frequency | 50-60 Hz |
| Power Factor | 0.7 - |
| Lamp Current mA | 53 mA |
| Dimmable | Yes |
| Wattage Equivalent | 40 W |
| Rated Wattage | 9.0 W |
| Starting Time | 0.5 (max) s |



| Warm-up Time to 60% Light Outp Suitable for accent | instant full light No |
|--|--------------------------|
| lighting | |
| Temperature Chara | cteristics |
| T-case maximum | 85 C |
| • Environmental chara | acteristics |
| Energy Efficiency Label (EEL) | A+ |
| Energy consumption kWh/1000h | n 9 kWh |
| Measuring Condition | ns |
| Switching cycle | 50000× |
| Product Dimensions | 5 |
| Overall Length C Diameter D | 110 mm 60 mm |
| • Product Data | |
| Order code | 929001150902 |
| Full product code | 929001150902 |
| Full product name | MASTER LEDbulb |
| Ouden end duct | A60 CL |
| Order product nam | CL |
| Pieces per pack | 1 |

DT 9-60W E27 9-60W E27 A60

Pieces per pack Packing configuration 10 Packs per outerbox 10



MASTER LEDbulb

| Bar code on pack - FAN1 | 8718696481325 |
|----------------------------|---------------|
| Bar code on | 8718696481332 |
| outerbox - EAN3 | |


Warnings and Safety

• Operating temperature range is between -20° C and 45° C ambient

Dimensional drawing

Logistic code(s) - 929001150902 12NC Net weight per piece 0.076 kg

- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights




MASTER LEDbulb DT 9-60W E27 A60 CL

| Product | C (Norm) | D (Norm) |
|-------------------------|----------|----------|
| LED DT 9-60W E27 A60 CL | 110 | 60 |



E27

Photometric data



DT 6-40W, 9-60W, ND 6.5-40W, 9.5-60W 2200-2700K A60 CL



© 2015 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting