

MASTER LEDtube InstantFit HF

MASTER LEDtube HF 1200mm HO 18W830 T8

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The MASTER LEDtube Performance is the ideal solution for customers which have higher light requirements and the want to maximize value over lifetime. (need the longest lifetime). Full energy savings and TCO benefits.

Product data

• General Characteristics

Main Application Industrial Cap-Base G13 Rated Lifetime 40000 hr (hours)

40000 hr

83

2000 Lm

70 %

Nominal Lifetime

hours

B50L70 40000

• Light Technical Characteristics

Color Code 830 160 D Beam Angle 3000 K Correlated Color

Temperature

Color rendering index

Rated Luminous Flux

LLMF - end nominal

lifetime

Colour consistency 6 steps Rated Beam Angle 160 D

• Electrical Characteristics

Wattage 18 W 50-100 V Voltage Line Frequency 25000/80000 Hz Power Factor 0.9 (min) -Dimmable Nο Rated Wattage 18.0 W 0.5 (max) s Starting Time 50-100 V Lamp voltage Warm-up Time to instant full light 60% Light Outp

Yes

Suitable for accent lighting

No

• Temperature Characteristics

T-case maximum 40 (max) C

-20 (min), 35 (max) C Operating tempera-

ture

T-Storage -40 (min), 65 (max) C

• Environmental characteristics

Energy Efficiency A+ Label (EEL) Energy consumption 22 kWh kWh/1000h

Measuring Conditions

Switching cycle 50000X

• Product Dimensions

Length A1 1198.0 mm Fixing Hole Distance 1205.0 mm

A2 Length

1212.0 mm Length A3 Mounting hole diam-25.6 mm

Circular outline 28 mm

dimension

• Approval & Application Chars

VDE marking No CE marking Yes UL certificate Nο



Energy saving

product



MASTER LEDtube InstantFit HF

RoHS compliance KEMA Keur certifi-

Yes Yes

cate

• Product Data

Order code 929001180002 Full product code 929001180002 Full product name MASTER LEDtu

MASTER LEDtube HF 1200mm HO

18W830 T8

Order product name MST LEDtube HF 1200mm HO

18W830 T8

Pieces per pack 1
Packing configuration 10
Packs per outerbox 10

Bar code on pack - 8718696514566 EAN1 Bar code on 8718696514573


Bar code on outerbox - EAN3

Logistic code(s) - 929001180002

12NC


Net weight per piece 0.360 kg

Dimensional drawing




MASTER LEDtube HF 1200mm HO 18W830 T8

Product	A (Norm)	A1 (Norm)	A2 (Norm)	A3 (Norm)	B (Min)	B (Norm)	B (Max)	D (Min)	D (Norm)	D (Max)	D1 (Norm)	D2 (Norm)
LEDtube HF 1200mm HO 18W830 T8	-	1198.0	1205.0	1212.0	-	-	-	-	-	-	25.6	28



G13

Photometric data



LEDtube HF 1200mm HO 18W /830 T8



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.