

CorePro LEDcandle

CorePro LEDcandle ND 3.5-25W E14 840 B35 FR

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.



CorePro LEDcandle

Product data

• General Information

Cap-Base E14 [E14]
Nominal Lifetime 15000 h
(Nom)
Switching Cycle 50000X
Technical Type 3.5-25W

• Light Technical


840 [CCT of 4000K (841)] Color Code Luminous Flux (Nom) Luminous Flux 290 lm (Rated) (Nom) Color Designation White (WH) Correlated Color 4000 K Temperature (Nom) 82.9 lm/W Luminous Efficacy (rated) (Nom) Color Consistency 6 steps Color Rendering Index (Nom) Llmf At End Of 70 %

• Operating and Electrical

Nominal Lifetime (Nom)

Input Frequency
Power (Rated)
(Nom)
Lamp Current (Nom)
Wattage Equivalent
Starting Time (Max)
Warm Up Time To
60% Light (Nom)
50-60 Hz
35 WA
25 W
0.5 s
instant full light

Dimensional drawing



Power Factor (Nom) 0.4 Voltage (Nom) 220-240 V

• Temperature

T-Case Maximum 70 °C (Nom)

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Bulb Finish Frosted (FR)

• Approval and Application

Suitable For Accent No Lighting Energy Efficiency A+ Label (EEL)

• Product Data

Full product code 871869654348100 CorePro LEDcandle ND 3.5-25W Order product name E14 840 B35 FR EAN/UPC - Product 8718696543481 Order code 929001205602 Numerator - Quantity Per Pack Numerator - Packs 10 per outer box . Material Nr. (12NC) 929001205602 Net Weight (Piece) 0.040 kg

LED ND 3.5-25W E14 840 B35 FR

 Product
 D
 C

 CorePro LEDcandle ND 3.5-25W E14 840 B35 FR
 35 mm
 106 mm

CorePro LEDcandle

Dimensional drawing





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.